


## BA304NG Type nA 2-wire 4-20mA 4 digit Indicator



- Ex nA & tc certified for use in Zones 2 & 22 hazardous areas
- Loop Powered – only 1.2V drop
- 4 digit 34mm high display
- Ex nA gas and Ex tc dust ATEX, IECEx, ETL & cETL certification
- IP66 GRP enclosure
- Root extractor and 16 segment lineariser
- Easy scale card installation on-site
- Optional backlight & alarms
- 3 year guarantee

## **BA304NG Type nA 2-wire 4-20mA 4 digit Indicator**

The BA304NG loop powered 4/20mA indicator is a new field mounting instrument that supersedes the well established BA304NC. It is electrically and mechanically compatible with the earlier model but has a much larger full 4 digit display, dust certification and guaranteed performance between -40 and +70°C. Like its predecessor, the BA304NG is housed in a robust IP66 enclosure which may be surface or pipe mounting.

Main application of the BA304NG is to display a measured variable in meaningful engineering units within a Zone 2 or 22 hazardous area. The zero and span of the display are independently adjustable allowing the indicator to be calibrated to display any linear variable represented by the 4/20mA signal. A root extractor and an adjustable sixteen segment lineariser enable the indicator to display flow and variables such as tank level in linear engineering units. For weighing applications a tare function is included.

A large 34mm high 4 digit display provides maximum contrast and has a very wide viewing angle, allowing the BA304NG indicator to be easily read in most lighting conditions over a wide temperature range. An optional factory fitted backlight is available for installations in poorly illuminated areas. The four digits, with three decimal points and a negative sign, may be configured to display any variable between -9999 and 9999.

IP66 protection is provided by the robust GRP enclosure which has stainless steel fittings, silicone gaskets and an 8mm thick armoured glass window. Ingress and impact protection have been independently assessed by Intertek. An optional back-box terminal assembly, including a continuity diode in the 4/20mA loop, is available for users wishing to terminate field wiring before the indicator assembly is installed.

The scale card which show units of measurement and tag information slides into an internal slot and can easily be changed on-site. New instruments are supplied with a printed scale card showing customer specified information, if this is not supplied a blank card is fitted which can easily be marked on-site.

IECEX, ATEX and ETL non sparking Ex nA certification allows the BA304NG to be installed in Zone 2 hazardous area without the need for Zener barriers or galvanic isolators. For Zone 2 applications the BA304NG offers a less expensive alternative to intrinsic safety and flameproof instrumentation.

Ex tc dust certification permits the BA304NG to be installed in Zone 22 dust hazardous areas, again without the need for Zener barriers or galvanic isolators.

## **BA304NG Type nA 2-wire 4-20mA 4 digit Indicator**

A backlight which may be loop or separately powered is available as a factory fitted option. It provides green background illumination allowing the display to be read at night or in poorly illuminated areas. When powered from the 4/20mA loop, no additional field wiring is required. Powering from a separate supply produces a brighter backlight but requires additional field wiring.

Optional dual alarm outputs which can switch hazardous or safe area loads, such as sounders, beacons or solenoid valves, are available as a factory fitted option. The two galvanically isolated solid state outputs may be independently conditioned as high or low alarms with normally open or closed outputs. Annunciators on the display show the status of both alarms.

Reliability is ensured by protection from incorrect connection and radio frequency interference. The indicator has been subjected to extensive vibration and thermal testing and is supported by a three year guarantee.

Other field mounting models in this range include the BA324NG which has a similar specification with a five digit 29mm high display plus a 31 segment bargraph.

### **Specification**

#### **Input**

Current	4 to 20mA HART® transparent
Voltage	Less than 1.2V at 20°C Less than 1.3V at -40°C Less than 5V with optional loop powered backlight
Overrange	±200mA or ±30V will not damage the indicator

#### **Display**

Type	Liquid Crystal, non-multiplexed 4 digits 34mm high
Span	Adjustable between 0 & ±9999 for a 4-20mA input
Zero	Adjustable between 0 & ±9999 with 4mA input
Decimal point	1 of 3 positions or absent
Polarity	Automatic minus sign
Zero blanking	Blanked apart from 0 in front of decimal point
Direction	Display may increase or decrease with increasing 4-20mA input
Reading rate	2 per second
Overrange	9999 or -9999 with all decimal points flashing

## BA304NG Type nA 2-wire 4-20mA 4 digit Indicator

### Push buttons

▼	(Function in display mode) Shows display with 4mA input
▲	Shows display with 20mA input
'P'	Displays unit in mA or % of span, has a modified function when alarms are fitted
'E'	Used for tare function

### Accuracy at 20°C

Linear	±0.02% of span ±1 digit
Root extracting	±16µA at input ±1 digit
Temperature effect on:	
Zero	Less than 25ppm of span/°C
Span	Less than 50ppm of span/°C
Series mode rejection	Less than 0.05% of span error for 1mA pk to pk 50 or 60Hz interference

### Intrinsic Safety

#### Europe ATEX

Code	Group II Category 3GD Ex nA ic IIC T5 Gc Ex tc IIIC T80°C Dc IP66 -40°C ≤ Ta ≤ 70°C ITS11ATEX47255
Cert. No.	

#### International IECEx

Code	Ex nA ic IIC T5 Gc Ex tc IIIC T80°C Dc IP66 -40°C ≤ Ta ≤ 70°C IECEx ITS11.0016
Cert. No.	

#### ETL & cETL USA & Canada

Code	Class I, Zone 2, AEx nA ic IIC T5 Gc Zone 22, AEx ic tc IIIC T80°C Dc -40°C ≤ Ta ≤ 60°C	]	USA
	Ex nA ic IIC T5 Gc: Ex n IIC T5 Gc Ex ic tc IIIC T80°C Dc -40°C ≤ Ta ≤ 60°C	]	Canada
ETL Control No.	4008610		

### Environmental

Operating Temperature	-40 to 70°C
Storage Temperature	-40 to 85°C
Humidity	to 95% at 40°C noncondensing
Enclosure	GRP IP66
EMC	Complies with EMC Directive 2014/30/EU

## BA304NG Type nA 2-wire 4-20mA 4 digit Indicator

### Mechanical


Terminals	Black with screw clamp for 0.5 to 1.5mm <sup>2</sup> cable
Weight	1.1kg

### Accessories


Backlight	Green, may be loop or separately powered
Loop powered	Indicator input voltage 5V
Separately powered	11V to 30V dc at 35mA
Alarms	Two alarm outputs, each of which may be independently configured as a high or low alarm contact with a NO or NC output
Output	Isolated solid state switch
V <sub>max</sub>	30V
I <sub>max</sub>	200mA
R <sub>on</sub>	5Ω + 0.7V max
R <sub>off</sub>	1MΩ min
Scale card	Slide-in card showing through display window units of measurement and tag information
Stainless steel legend plate	Stainless steel plate laser engraved with tag number or application information attached to rear of instrument, visible from the front
Terminal assembly	Mounted in enclosure back-box for terminating field wiring before indicator assembly is installed. Includes continuity diode in 4-20mA loop.
Pipe mounting kit	BA393G 316 Stainless Steel
Panel mounting kits	BA394G stainless steel not sealing

## BA304NG Type nA 2-wire 4-20mA 4 digit Indicator

### Dimensions



### Terminal Connections



## BA304NG Type nA 2-wire 4-20mA 4 digit Indicator

### Ordering Information

	<b>Please specify</b>
Model Number	BA304NG
Display mode	Linear, root or lineariser <i>Will be set to display 0.0 at 4mA and 100.0 at 20mA with a linear display if calibration information is not supplied. Can easily be recalibrated on-site.</i>
Display at:	
4.000mA	<i>Include position of decimal point &amp; sign if negative, plus intermediate points if linearization is required</i>
20.000mA	
<b>Accessories</b>	<b>Please specify if required</b>
Display backlight	Backlight
Dual alarms	Alarms
Scale card marking	
Units	Legend required
Tag	Legend required
Stainless Steel legend plate	Legend required
Back-box terminal assembly	Terminal assembly
Pipe mounting kit	BA393G
Panel mounting kit	BA394G